

HD-TVI MOTORIZED TURRET DOME

LTBT2812EXIR-MZ



Features

- High Definition 2 Megapixel 1080p
- Motorized Varifocal Lens
- 2.8~12mm Adjustable from Recorder
- HD-TVI Technology
- True Wide Dynamic Range
- Outdoor Rated (IP66)
- New EX-IR 150ft IR Range
- Up the Coax OSD Control
- Up to 1,500ft Coaxial Transmission
- Up to 600ft Twisted Pair Transmission
- Smart IR
- DC 12V

Part Number	LTBT2812EXIR-MZ
Resolution	2 Megapixel / 1920(H) x 1080(V)
Frame Rate	30fps@1080p
Image Sensor	1/3" Progressive Scan CMOS
Lux Rating	0.01 Lux @ F1.2 AGC On, 0.0 Lux with IR On
Shutter	1/30s ~ 1/50,000s
Lens	2.8-12mm, Angle of View 92° - 32°
Angle Adjustment	Pan: 0-360°, Tilt: 0-90°, Rotation: 0-360°
IR Range	150ft
Lens Mount	M12
DNR	3D x DNR
WDR	True
BLC	Supported
Day/Night	True Day/Night
Synchronization	Internal
HD Video Output	1 Analog HD-TVI Output
CVBS Output	N/A - No analog output
Power	DC 12V, 5W
Weatherproof	IP66 Rated
Dimensions	4.33" x 3.67"
Weight	.77 lbs.
Operating Temp	-4 °F ~ 140 °F, Humidity 90%