

VLBCM5MEXIR28



FEATURES

HD 4-in-1 5MP Exterior IR Bullet

- 5MP video output
- HD 4-in-1 Technology (TVI/CVI/AHD/CVBS)
- DWDR
- True Day/Night
- OSD menu(UTC), DNR, Smart IR
- 60 ft IR distance
- IP67 weatherproof

Specifications	
Model Number	VLBCM5MEXIR28
Image Sensor:	5MP CMOS
Video Format	PAL/NTSC
Effective Pixels:	2560(H)*1944(V)
Min. Illumination	0.01 Lux @ (F1.2, AGC ON),0 Lux with IR
Shutter Time	1/30 s to 1/50,000 s
Lens:	2.8mm
Adjustment Range:	Pan: 0 - 355°, Tilt: 0 - 75°
Day& Night:	IR cut filter with auto switch
Wide Dynamic Range:	DWDR
Video Frame Rate:	2560*1944 @ 20fps
HD Video Output:	1 HD output (TVI/CVI/AHD/CVBS)
CVBS Output	Support

Specifications	
D/N Mode	Color/BW/Auto
Working Temperature / Humidity	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply:	12 V DC±25%
Power Consumption:	Max. 4.3W
Weather Proof:	IP67
IR Range	Up to 60 ft
Dimensions	2.18" x 2.30" x 6.04"
Weight:	0.77 lbs
Electrical Box	JNBX1
Pole Mount	IPPOLEMT
Corner Mount	CRNMT