

HD 4-1 ANALOG TURRET DOME

LGBT28EXIR



Features

- 4 Selectable Outputs
 - TVI / CVI / AHD / CVBS
- HD 2 Megapixel 1080p
- 2.8mm Fixed Lens
- EXIR 65ft IR Range
- Outdoor Weatherproof Rated (IP66)
- Wide Dynamic Range
- 3xDigital Noise Reduction
- Up to 1,500ft Coaxial Transmission
- Up to 600ft Twisted Pair Transmission w/Balun
- Value Line Series - 2 Year Warranty
- 12vDC

| Part Number | LGBT28EXIR |
|-------------------|--|
| Resolution | HD 1080p / 2.4 Megapixel |
| Frame Rate | 30fps@1080p |
| Image Sensor | 1/2.9" 2 Megapixel CMOS |
| Effective Pixels | 1920(H) x 1088(V) |
| Housing | White |
| Min. Illumination | 0.01 (AGC On), 0.0 Lux with IR on |
| Lens | 2.8mm Fixed Lens |
| IR LEDs | EXIR |
| IR Range | 65ft Range |
| Day/Night | IR Cut Filter |
| Noise Reduction | 3DNR |
| WDR | True Wide Dynamic Range |
| Signal System | NTSC / PAL |
| Trans. Distance | Up to 1,500ft over coax / 600ft over twisted pair CAT5/6 w/Balun |
| BNC Output | TVI/CVI/AHD/Standard Analog(CVBS) |
| Signal Control | Joystick |
| Outdoor Rating | Weatherproof (IP66) |
| Dimension | 3.72" x 3.72" x 2.99" (H) |
| Operating Temp. | -10°C ~ +50°C RH95% MAX |
| Weight | 0.99 lbs. |
| Power Supply | 12vDC±10%, 500mA |