

## Model: IPB2MLRIR49

2 Megapixel IP Long Range IR Bullet



- 2 Megapixel (1920 x 1080) Resolution
- Full HD 1080p 60fps recording
- True WDR & 3D DNR & BLC
- Audio & Alarm I/O's
- EXIR illuminators: up to 360ft
- Built-in Micro SD/SDHC/SDXC card slot, up to 128 GB
- IP67
- 30X optical zoom lens 4.7 – 94mm

Image Sensor	1/2.8" progressive scan CMOS
Min. illumination	0.005 Lux @ (F1.4, AGC ON), 0 Lux with IR
Shutter time	1s ~ 1/100.000s
Lens	4.7 – 94 mm @ F1.4 Motorized VF lens
Day & night	ICR
Digital noise reduction	3D DNR
Wide dynamic range	True WDR
Backlight compensation	Yes, zone configurable
Video compression	H.265+ / H.265 / H.264 / H.264+ / MJPEG / MPEG4
Bit rate	32 Kbps ~ 16 Mbps
Max. image resolution	1920 x 1080
Frame rate	60Hz: 60fps (1920 x 1080), 60fps (1280 x 720)
On board Storage	Built-in Micro SD/SDHC/SDXC card slot, up to 128 GB
Alarm trigger	Motion detection, tampering alarm
System compatibility	ONVIF, PSIA, CGI
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Operating conditions	-30°C ~ 60°C (-22°F ~ 140°F) humidity 90% or less (non-condensing)
Power supply	12 VDC ± 10%, PoE (802.3at)
Power consumption	Max. 18W
Dimensions	100×103.9×311.8mm (3.93"×4.09"×12.28")
Weight	2000g (4.41 lbs)
Electrical Box	GBX2
Pole	IPPOLEMT
Corner	CRNMT